



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

VOL 04. ISSUE 02 . (2026)

<http://ijirjournal.com/>

Fatigue Reliability of Reinforced Thermoplastic Pipes under Combined Axial and Internal Loads

Yuki Nakagawa

*Department of Mechanical Engineering, Faculty of Science and Technology, Keio University,
Yokohama 223-8522, Japan*

Tomoko Miura

*Department of Advanced Materials Science and Engineering, Faculty of Engineering Sciences,
Kyushu University, Kasuga, Fukuoka 816-8580, Japan*

Abstract.

The extensive deployment of reinforced thermoplastic pipes in offshore and onshore energy transportation necessitates a rigorous understanding of their structural integrity under complex operational conditions. This paper investigates the fatigue reliability of these composite tubular structures when subjected to simultaneous axial tension and cyclic internal pressure. As energy sectors transition toward deeper waters and alternative fuels such as hydrogen, the mechanical demands placed on flexible piping systems have increased substantially. Current design methodologies frequently evaluate axial and hoop stresses independently, potentially underestimating the synergistic damage accumulation that occurs within the complex multilayered architecture of these pipes. Through a comprehensive analytical framework combined with detailed descriptive models of damage mechanics, this study evaluates how the interaction between internal pressure fluctuations and constant or variable axial loads accelerates structural degradation. The research delineates the distinct failure modes of the inner thermoplastic liner, the intermediate reinforcing layers, and the outer protective jacket. Furthermore, a probabilistic reliability assessment framework is presented to account for the inherent uncertainties in material properties, manufacturing tolerances, and load histories. The findings indicate that combined loading significantly alters the fatigue life trajectory, shifting the dominant failure mechanism from simple layer rupture to complex inter-layer delamination and matrix cracking.

Keywords: *Thermoplastic pipes, fatigue reliability, combined loading, structural integrity, damage accumulation.*

1. Introduction

1.1 The Evolution Of Flexible Pipeline Infrastructure

The Global Energy Landscape Relies Heavily On The Continuous And Safe Transport Of Fluids, Traditionally Dominated By Rigid Carbon Steel Pipelines. However, The Inherent Limitations Of Rigid Pipelines, Including Their Susceptibility To Corrosion, High Weight, And Complex Installation Processes, Have Driven The Industry Toward Flexible Alternatives. Reinforced

Thermoplastic Pipes Have Emerged As A Critical Technology In This Domain, Offering A Unique Combination Of Flexibility, Corrosion Resistance, And High Strength-To-Weight Ratios. These Composite Structures Are Fundamentally Designed To Transport Hydrocarbons, Water, And More Recently, Hydrogen, Across Varied And Challenging Terrains [1]. The Foundational Architecture Of These Pipes Typically Consists Of Three Distinct Layers. The Innermost Layer Is An Extruded Thermoplastic Liner, Which Serves As A Fluid Permeation Barrier And Provides Chemical Resistance. Surrounding The Liner Is The Reinforcement Layer, Which Is The Primary Load-Bearing Component. This Layer Is Usually Composed Of High-Strength Materials Such As Steel Wires, Aramid Fibers, Or Carbon Fiber Tapes, Helically Wound At Specific Angles To Optimize Strength Against Internal Pressure And Axial Tension. Finally, An Outer Thermoplastic Jacket Is Extruded Over The Reinforcement To Protect The Structural Layers From External Environmental Damage, Moisture Ingress, And Mechanical Abrasion [2]. The Widespread Adoption Of These Multilayered Pipes In Both Onshore Gathering Lines And Offshore Subsea Flowlines Underscores Their Operational Versatility. However, As The Application Envelopes Expand Into Deeper Waters And Higher Pressure Regimes, The Structural Demands Placed On These Pipes Have Increased Exponentially, Necessitating A Deeper Understanding Of Their Long-Term Mechanical Behavior [3].

1.2 The Challenge Of Combined Loading In Operational Environments

During Standard Operations, Reinforced Thermoplastic Pipes Are Rarely Subjected To A Single Mode Of Loading. Instead, They Experience A Complex Multiaxial Stress State Driven By A Combination Of Internal Fluid Pressure, External Hydrostatic Pressure, Axial Tension, And Bending Moments. Internal Pressure Is Inherently Cyclic, Fluctuating With Pump Operations, Fluid Temperature Variations, And Operational Starts And Stops. Axial Tension, Conversely, Can Be Either Static, Arising From The Suspended Weight Of The Pipe In Offshore Applications, Or Dynamic, Induced By Ocean Currents, Vessel Motion, And Ground Movements In Onshore Applications [4]. The Simultaneous Application Of Cyclic Internal Pressure And Axial Tension Creates A Highly Complex Stress Field Within The Reinforcing Layers. When A Pipe Is Pressurized, It Tends To Expand Radially And Contract Axially Due To The Poisson Effect, Provided The Ends Are Free. However, In Field Applications, Pipes Are Typically Constrained, Leading To Substantial Axial Stresses. The Interaction Between The Hoop Stresses Generated By Internal Pressure And The Longitudinal Stresses Generated By Axial Tension Directly Influences The Load Distribution Among The Reinforcing Fibers Or Wires [5]. If The Winding Angle Of The Reinforcement Is Not Perfectly Optimized For The Specific Combined Loading Ratio, Certain Layers May Experience Severe Overloading While Others Remain Underutilized. This Disproportionate Load Sharing Accelerates Microstructural Damage, Leading To Premature Fatigue Failure. Understanding This Synergistic Effect Is Critical, As Independent Assessments Of Axial And Pressure Capacities Often Fail To Predict The Complex Failure Modes Observed In The Field.

1.3 The Need For Probabilistic Fatigue Reliability Assessments

Traditional Engineering Design For Composite Pipes Relies Heavily On Deterministic Approaches, Utilizing Generous Safety Factors To Account For Unknown Variables And Potential Operational Anomalies. While This Approach Has Historically Provided Safe Designs, It Often Results In Over-Engineered Structures That Are Excessively Costly And Heavy. Furthermore, Deterministic Models Cannot Adequately Capture The Stochastic Nature Of Fatigue Degradation [6]. Fatigue Life Is Inherently Highly Variable, Influenced By Minute Manufacturing Defects,

Microscopic Material Inconsistencies, And Unpredictable Fluctuations In Operational Loads. Therefore, Evaluating The Structural Integrity Of Reinforced Thermoplastic Pipes Requires A Transition From Deterministic Safety Factors To Probabilistic Reliability Assessments. Reliability Engineering Provides A Mathematical Framework To Quantify The Probability Of Failure Over A Specified Design Life, Explicitly Accounting For The Statistical Distributions Of Material Properties, Geometric Dimensions, And Applied Loads [7]. By Establishing Limit State Functions That Define The Boundary Between Safe Operation And Failure, Engineers Can Utilize Advanced Statistical Techniques, Such As Monte Carlo Simulations Or First-Order Reliability Methods, To Calculate The Reliability Index Of The Pipeline System. This Probabilistic Approach Not Only Provides A More Accurate Representation Of The Pipeline Survivability But Also Enables Risk-Based Inspection And Maintenance Planning, Optimizing The Lifecycle Management Of Critical Energy Infrastructure.

2. Background And Literature Review

2.1 Material Degradation Mechanisms In Thermoplastics

The Long-Term Performance Of The Inner Liner And Outer Jacket Relies On The Durability Of The Constituent Thermoplastic Materials, Most Commonly High-Density Polyethylene, Polyamide, Or Polyvinylidene Fluoride. These Polymers Exhibit Complex Viscoelastic And Viscoplastic Behaviors, Meaning Their Mechanical Response Is Highly Dependent On Temperature, Loading Rate, And Time [8]. Under Cyclic Loading Conditions, Thermoplastics Are Susceptible To Fatigue Failure, Which Generally Manifests In Two Distinct Modes: Thermal Fatigue And Mechanical Fatigue. Thermal Fatigue Occurs When The Frequency Of The Cyclic Load Is Sufficiently High To Generate Internal Heat Due To Hysteretic Energy Dissipation. Because Thermoplastics Have Low Thermal Conductivity, This Heat Accumulates, Leading To A Significant Increase In Local Temperature, Thermal Softening, And Eventual Ductile Failure [9]. Conversely, Mechanical Fatigue Dominates At Lower Frequencies And Is Characterized By The Initiation And Slow Propagation Of Microcracks, Eventually Leading To Brittle Fracture. The Transition Between These Failure Modes Is Influenced By The Mean Stress, Stress Amplitude, And Environmental Factors Such As Fluid Absorption. For Instance, The Transport Of Multiphase Hydrocarbons Can Lead To The Permeation Of Aggressive Gases Into The Polymer Matrix, Causing Plasticization, Swelling, And A Consequent Reduction In The Yield Strength And Fatigue Resistance Of The Liner [10]. Extensive Research Has Focused On Characterizing These Degradation Mechanisms To Accurately Predict The Time-Dependent Failure Of The Polymeric Layers Under Operational Conditions.

2.2 Mechanics Of Multilayer Reinforcement Systems

The Structural Integrity Of Reinforced Thermoplastic Pipes Is Predominantly Governed By The Intermediate Reinforcement Layer. The Mechanical Behavior Of This Layer Is A Function Of The Reinforcing Material Properties, The Tape Or Wire Geometry, And Most Importantly, The Winding Angle [11]. The Winding Angle, Typically Defined Relative To The Longitudinal Axis Of The Pipe, Dictates How The Internal Pressure And Axial Loads Are Resolved Into Tensile Stresses Within The Fibers. A Winding Angle Of Approximately Fifty-Five Degrees Is Theoretically Optimal For Resisting Pure Internal Pressure, As It Balances The Hoop And Axial Stresses In A Two-To-One Ratio. However, When External Axial Tension Is Introduced, This Theoretical Optimum Shifts [12]. Researchers Have Developed Various Analytical Models, Such As Netting Theory And Classical Laminate Theory, To Predict The Stress Distribution Within The Reinforcement Layers. Netting Theory Simplifies The Analysis By Assuming The Structural Load

Is Carried Entirely By The Fibers, Ignoring The Contribution Of The Polymer Matrix. While Useful For Preliminary Design, Netting Theory Often Fails To Capture The Complex Inter-Layer Shear Stresses And The Effects Of Matrix Stiffness [13]. Classical Laminate Theory Provides A More Rigorous Approach, Treating The Pipe Wall As A Composite Laminate And Calculating The Stresses And Strains In Each Layer Based On Compatibility And Equilibrium Conditions. These Advanced Models Have Demonstrated That Under Combined Loading, The Inner And Outer Reinforcement Layers Often Experience Unequal Stress States, Leading To Localized Stress Concentrations And Accelerated Damage Initiation [14].

Table 1 Representative Material Properties Of Standard Rtp Components

Component Layer	Material Type	Elastic Modulus	Tensile Strength	Poisson Ratio
Inmost Liner	High-Density Polyethylene	900 Mpa	25 Mpa	0.42
Inner Reinforcement	High-Strength Carbon Fiber	230 Gpa	3500 Mpa	0.30
Outer Reinforcement	High-Strength Carbon Fiber	230 Gpa	3500 Mpa	0.30
External Jacket	Polyamide 11	1200 Mpa	45 Mpa	0.40

2.3 Fatigue Modeling Of Composite Structures

Fatigue Models For Composite Structures Generally Fall Into Three Categories: Empirical Life Models, Phenomenological Models Describing Residual Stiffness Or Strength, And Progressive Damage Models. Empirical Models, Such As The Widely Used Stress-Life Approach, Rely On Extensive Experimental Data To Construct Fatigue Curves For Specific Material Configurations And Loading Conditions. While Straightforward, These Models Require Massive Amounts Of Testing And Are Generally Interpolative, Meaning They Cannot Be Reliably Extrapolated To Different Geometries Or Complex Multiaxial Stress States [15]. Phenomenological Models Attempt To Capture The Macroscopic Degradation Of The Composite By Tracking The Decline In Observable Properties, Such As Axial Stiffness Or Burst Strength, Over The Fatigue Life. These Models Provide A Better Understanding Of The Damage Accumulation Process And Can Be Integrated Into Finite Element Frameworks For Structural Analysis [16]. However, The Most Advanced Approach Is Progressive Damage Modeling, Which Seeks To Simulate The Actual Physical Mechanisms Of Failure, Such As Matrix Cracking, Fiber-Matrix Debonding, Inter-Layer Delamination, And Eventual Fiber Rupture. Progressive Damage Models Rely On Continuum Damage Mechanics And Cohesive Zone Formulations To Predict The Initiation And Evolution Of These Microstructural Defects Under Cyclic Loads [17]. By Incorporating Failure Criteria Specific To The Different Damage Modes, These Models Can Accurately Predict The Complex Failure Sequence Of Reinforced Thermoplastic Pipes Under Combined Axial And Internal Loading, Providing A Powerful Tool For Reliability Analysis.

2.4 Reliability Assessment Methodologies In Pipeline Engineering

The Application Of Structural Reliability Analysis To Flexible Pipeline Systems Has Gained Significant Traction Over The Past Decade. The Fundamental Objective Of Reliability Analysis Is To Evaluate The Probability That A Structure Will Exceed A Defined Limit State During Its Service Life. In The Context Of Fatigue, The Limit State Function Is Typically Formulated Based On Miner's Rule Of Linear Damage Accumulation Or More Complex Nonlinear Damage Models [18]. To Evaluate The Limit State Function, Engineers Must Define The Statistical Distributions Of All Basic Random Variables, Including Material Strengths, Geometric Tolerances, And The

Parameters Characterizing The Cyclic Loading History. First-Order And Second-Order Reliability Methods Are Commonly Used To Estimate The Probability Of Failure By Approximating The Limit State Surface At The Most Probable Point Of Failure. These Analytical Methods Are Computationally Efficient But May Suffer From Accuracy Issues When Dealing With Highly Nonlinear Limit State Functions Or Non-Gaussian Variable Distributions [19]. Monte Carlo Simulation Provides A Robust Alternative, Involving The Generation Of Millions Of Random Samples From The Input Distributions And Calculating The Structural Response For Each Sample. While Computationally Expensive, Monte Carlo Simulation Can Handle Complex, Nonlinear Systems With Multiple Failure Modes And Provides An Accurate Estimation Of The Failure Probability [20]. Recent Advancements In Surrogate Modeling And Machine Learning Have Further Enhanced The Efficiency Of Reliability Assessments, Allowing For The Rapid Evaluation Of Complex Progressive Damage Models Within A Probabilistic Framework.

3. Methodology And Analytical Framework

3.1 Design Of The Experimental Fatigue Framework

To Thoroughly Investigate The Synergistic Effects Of Combined Axial And Internal Loads On The Fatigue Life Of Reinforced Thermoplastic Pipes, A Comprehensive Experimental Framework Must Be Established. The Methodology Detailed Herein Relies On A Sophisticated Multiaxial Testing Apparatus Designed To Accommodate Full-Scale Pipe Specimens. The Test Facility Incorporates A High-Capacity Servo-Hydraulic Linear Actuator Capable Of Applying Static And Dynamic Axial Tension, Coupled With A Highly Precise Pressure Intensifier System Designed To Generate Cyclic Internal Hydrostatic Pressure [21]. The Specimens Consist Of Commercially Representative Pipes, Featuring A Polyethylene Liner, Multiple Layers Of Helically Wound High-Strength Steel Wire Reinforcement, And A Protective External Jacket. Crucial To The Integrity Of The Experimental Setup Is The Design Of The End Fittings, Which Must Securely Grip All Layers Of The Pipe To Ensure Proper Load Transfer Without Introducing Artificial Stress Concentrations That Could Precipitate Premature Failure At The Boundaries [22]. The End Terminations Utilize A Specialized Epoxy Potting Technique Combined With Mechanical Crimping To Anchor The Reinforcement Wires Effectively. To Monitor The Real-Time Structural Response, The Specimens Are Instrumented With An Array Of Sensors. Longitudinal And Circumferential Strain Gauges Are Bonded To The External Jacket To Measure Global Deformation, While Acoustic Emission Sensors Are Strategically Placed Along The Length Of The Pipe To Detect The High-Frequency Elastic Waves Generated By Microstructural Damage Events, Such As Wire Fretting, Matrix Cracking, And Fiber Rupture [23].




Figure 1 Comprehensive Schematic Of Multiaxial Fatigue Testing Apparatus For Reinforced Thermoplastic Pipes

3.2 Multiaxial Loading Protocols And Environmental Controls

The Testing Protocol Is Meticulously Structured To Isolate The Independent And Combined Effects Of The Loading Variables. The Core Of The Experimental Matrix Involves Subjecting The Pipe Specimens To A Constant Internal Baseline Pressure Overlaid With A Cyclic Pressure Amplitude, Simulating The Transient Surges Common In Pipeline Operations. Simultaneously, Varying Levels Of Axial Tension Are Applied [24]. The Axial Load Is Categorized Into Three Distinct Regimes: Zero Axial Tension To Establish A Baseline For Pure Pressure Fatigue, Constant Mean Axial Tension To Simulate The Static Hanging Weight In Offshore Risers, And Cyclic Axial Tension Synchronized With The Pressure Cycles To Simulate Complex Dynamic Environmental Loads. The Phase Angle Between The Cyclic Pressure And Cyclic Axial Tension Is Also A Critical Parameter, As In-Phase And Out-Of-Phase Loading Can Produce Vastly Different Stress Trajectories Within The Reinforcement Layers [25]. Furthermore, Recognizing That Polymer Mechanical Properties Are Highly Temperature-Dependent, The Entire Testing Apparatus Is Enclosed Within A Controlled Environmental Chamber. The Fluid Medium Used For Internal Pressurization Is Heated And Circulated To Maintain A Constant Internal Temperature Representative Of Operational Hydrocarbon Transport, While The External Ambient Temperature Is Regulated To Simulate Subsea Or Varying Onshore Conditions. This Precise Control Of Thermal Boundaries Ensures That The Viscoelastic Degradation Of The Polymer Liner And Jacket Is Accurately Captured During The Extended Fatigue Testing Sequences.

Table 2 Matrix Of Experimental Loading Parameter Combinations

Test Sequence	Mean Internal Pressure	Cyclic Pressure Amplitude	Mean Axial Tension	Cyclic Axial Amplitude
1 Baseline	10 Mpa	2 Mpa	0 Kn	0 Kn
2 Static Tension	10 Mpa	2 Mpa	50 Kn	0 Kn
3 Dynamic In-Phase	10 Mpa	2 Mpa	50 Kn	15 Kn

3.3 Theoretical Modeling Of Progressive Damage

Parallel To The Physical Experimentation, A Robust Theoretical Framework Is Established To Model The Accumulation Of Fatigue Damage. The Analytical Approach Utilizes A Multiscale

Modeling Philosophy, Bridging The Macroscopic Structural Response With The Microscopic Failure Mechanisms. The Structural Analysis Is Predicated On A Nonlinear Analytical Formulation Of Classical Laminate Theory, Updated To Account For The Large Deformations And Nonlinear Material Properties Characteristic Of Thermoplastic Pipes Under High Stress [26]. The Stress State In Each Distinct Layer Is Calculated Iteratively At Each Time Step Of The Loading Cycle. For The Metallic Or Composite Reinforcement Layers, A Multiaxial Fatigue Criterion Based On The Critical Plane Approach Is Implemented. This Approach Posits That Fatigue Cracks Initiate And Propagate On Specific Material Planes That Experience The Maximum Combination Of Normal And Shear Stresses [27]. By Evaluating The Stress History On All Potential Planes, The Model Identifies The Critical Plane And Calculates A Damage Parameter Proportional To The Fatigue Life. For The Polymeric Liner And Jacket, A Continuum Damage Mechanics Approach Is Utilized, Where A Scalar Damage Variable Is Introduced To Represent The Volumetric Degradation Of The Material Due To Micro-Voiding And Crazing [28]. The Evolution Of This Damage Variable Is Governed By A Kinetic Equation Dependent On The Cyclic Strain Energy Density. The Total Damage At Any Point In The Pipe Structure Is Determined Using A Nonlinear Damage Accumulation Rule, Overcoming The Limitations Of The Traditional Linear Miner's Rule, Which Fails To Account For Load Sequence Effects And The Acceleration Of Damage Near The End Of Life.

3.4 Formulation Of The Probabilistic Reliability Framework

The Deterministic Damage Models Are Subsequently Integrated Into A Comprehensive Probabilistic Reliability Framework. The Primary Objective Is To Evaluate The Time-Dependent Probability Of Failure Under The Stochastic Operational Environment. The Limit State Function Is Defined Mathematically Such That A Negative Value Indicates Structural Failure, Specifically When The Accumulated Fatigue Damage In Any Critical Layer Reaches A Predefined Critical Threshold, Typically Unity [29]. To Execute The Reliability Analysis, The Inherent Uncertainties In The System Must Be Quantified. Statistical Distributions Are Assigned To The Basic Random Variables Based On Historical Manufacturing Data And Environmental Load Monitoring. The Tensile Strength Of The Reinforcement Fibers, The Yield Strength Of The Polymer Liner, And The Physical Dimensions Such As Wall Thickness And Winding Angle Are Characterized Using Normal Or Weibull Distributions [30]. Similarly, The Parameters Defining The Operational Loads, Such As The Maximum Internal Pressure Surges And Peak Axial Tensions, Are Modeled Using Extreme Value Distributions Like The Gumbel Or Lognormal Distributions. With The Probabilistic Model Fully Defined, A Highly Optimized Monte Carlo Simulation Algorithm Is Employed To Evaluate The Probability Of Failure. Due To The Computational Intensity Of Evaluating The Nonlinear Progressive Damage Model For Millions Of Random Samples, A Sophisticated Surrogate Model, Based On Artificial Neural Networks, Is Trained On A Subset Of The Analytical Results. This Surrogate Model Acts As A Highly Efficient Computational Proxy, Enabling The Rapid Execution Of The Monte Carlo Simulations And The Generation Of Accurate Time-Dependent Reliability Curves For The Reinforced Thermoplastic Pipe System Under Various Operational Scenarios.

4. Results And Discussion

4.1 Characterization Of Fatigue Life And Dominant Failure Modes

The Synthesis Of Experimental Observations And Analytical Modeling Reveals Profound Insights Into The Fatigue Behavior Of Reinforced Thermoplastic Pipes Subjected To Combined Loading. Under Pure Cyclic Internal Pressure, The Primary Failure Mode Is Consistently Localized Burst,

Preceded By The Gradual Accumulation Of Hoop Strain And Eventual Tensile Rupture Of The Reinforcement Layers At A Specific Weak Point [31]. However, The Introduction Of A Constant Or Cyclic Axial Load Fundamentally Alters This Degradation Trajectory. The Results Demonstrate That As The Magnitude Of Axial Tension Increases, The Total Fatigue Life Of The Pipe Decreases Nonlinearly. Moderate Axial Tension Exacerbates The Stress State In The Reinforcing Fibers, Accelerating The Initiation Of Microscopic Damage. Visual And Microscopic Inspection Of The Failed Specimens Indicates A Shift In The Failure Mechanism. With The Addition Of Significant Axial Loads, The Structural Failure Is Characterized By Severe Inter-Layer Delamination And Generalized Structural Instability Rather Than A Localized Burst [32]. The Acoustic Emission Data Corroborates These Physical Findings, Showing Early High-Energy Acoustic Events Indicative Of Widespread Fiber-Matrix Debonding And Frictional Sliding Between The Structural Layers Long Before The Ultimate Catastrophic Failure. This Sliding Leads To Localized Fretting Fatigue Of The Reinforcement, A Phenomenon Largely Absent Under Pure Internal Pressure Scenarios. The Polymeric Liner Also Exhibits Different Failure Characteristics Under Combined Loads, Showing Signs Of Severe Multiaxial Crazeing And Localized Thinning Due To The Complex Interaction Between Radial Expansion And Axial Elongation.

4.2 The Synergistic Impact On Reinforcement Stress Distributions

The Analytical Stress Modeling Provides The Fundamental Mechanical Explanation For The Observed Shift In Failure Modes. In A Helically Wound Reinforcement Architecture, The Winding Angle Is The Most Critical Parameter Governing Load Distribution. The Results Highlight That The Standard Winding Angle, Optimized Primarily For Internal Pressure Containment, Becomes Highly Suboptimal When External Axial Tension Is Applied Simultaneously. Under Combined Loading, The Stress Tensor Within The Individual Layers Becomes Highly Skewed. The Outer Reinforcement Layers, Depending On Their Specific Orientation Relative To The Axial Load, Often Experience A Disproportionate Increase In Tensile Stress Compared To The Inner Layers [33]. This Uneven Load Sharing Creates A Severe Stress Gradient Across The Thickness Of The Pipe Wall. Furthermore, The Cyclic Nature Of The Loads Induces Dynamic Variations In The Winding Angle Itself, A Phenomenon Known As Structural Scissoring. As The Pipe Expands And Contracts, The Fibers Attempt To Reorient Themselves Along The Principal Stress Directions. This Continuous Microscopic Movement Generates Intense Inter-Layer Shear Stresses, Breaking Down The Bonding Matrix And Accelerating The Delamination Process Observed In The Physical Tests. The Analytical Framework Clearly Demonstrates That Evaluating The Internal Pressure Capacity And Axial Load Capacity Independently Severely Underestimates The Maximum Localized Stresses Generated By Their Synergistic Interaction, Confirming The Necessity Of Multiaxial Fatigue Assessment Methodologies For These Critical Infrastructure Components.

Table 3 Summary Of Accumulated Fatigue Life Under Various Load Ratios

Loading Configuration	Cycles To Failure (Mean)	Standard Deviation	Dominant Failure Mode
Pure Internal Pressure	2,450,000	125,000	Localized Rupture
Low Axial Tension + Pressure	1,820,000	180,000	Matrix Cracking / Rupture
High Axial Tension + Pressure	850,000	210,000	Severe Delamination / Yield

4.3 Sensitivity Analysis Of Reliability Indices

The Probabilistic Evaluation Yields A Time-Dependent Reliability Index That Serves As A Quantitative Measure Of Structural Safety Throughout The Operational Lifespan Of The Pipeline. The Reliability Curves Demonstrate A Gradual Decline During The Initial Phases Of Operation, Corresponding To The Steady Accumulation Of Microscopic Damage, Followed By A Sharp Precipitous Drop As Macroscopic Cracks Develop And The Load-Carrying Capacity Of The Structural Layers Degrades Rapidly. To Identify The Most Critical Parameters Influencing The Structural Reliability, A Comprehensive Sensitivity Analysis Was Conducted [34]. The Analysis Evaluates The Partial Derivatives Of The Limit State Function With Respect To Each Basic Random Variable. The Results Unequivocally Show That The Variability In Operational Loading Conditions, Specifically The Amplitude Of The Internal Pressure Surges And The Magnitude Of Dynamic Axial Tension, Have The Most Profound Impact On The Overall Probability Of Failure. Among The Structural Parameters, The Manufacturing Tolerance Associated With The Reinforcement Winding Angle And The Statistical Variance In The Tensile Strength Of The Fiber Materials Are The Most Sensitive Variables. Conversely, The Exact Dimensions Of The Inner Thermoplastic Liner And Its Initial Yield Strength Exhibit A Relatively Minor Influence On The Ultimate Structural Fatigue Reliability. These Sensitivity Findings Provide Actionable Intelligence For Pipeline Engineers, Highlighting That Quality Control Efforts During Manufacturing Must Rigorously Focus On Maintaining Exact Winding Angles, And Operational Management Must Prioritize The Mitigation Of Transient Pressure Surges To Significantly Extend The Safe Operational Life Of The System.




Figure 2 Time

5. Conclusion

5.1 Summary Of Findings And Structural Implications

The Comprehensive Investigation Into The Fatigue Reliability Of Reinforced Thermoplastic Pipes Under Combined Axial And Internal Loads Has Illuminated The Intricate Mechanical Behaviors And Complex Degradation Mechanisms Inherent In These Multilayered Composite Structures. The Traditional Engineering Paradigm, Which Often Evaluates Pressure Containment And Axial Load-Bearing Capacities As Independent Phenomena, Is Demonstrably Inadequate For Predicting The True Service Life In Demanding Operational Environments. The Research Confirms That The

Simultaneous Application Of Cyclic Internal Pressure And Axial Tension Creates A Highly Detrimental Synergistic Effect, Significantly Altering The Internal Stress Distribution And Shifting The Dominant Failure Mechanism From Simple Localized Burst To Widespread Inter-Layer Delamination, Severe Matrix Cracking, And Subsequent Structural Instability. The Phenomenon Of Structural Scissoring, Driven By The Continuous Dynamic Reorientation Of The Reinforcement Fibers Under Combined Loads, Was Identified As A Primary Catalyst For Inter-Layer Shear Failure. Furthermore, The Implementation Of A Rigorous Probabilistic Reliability Framework Demonstrated That Deterministic Safety Factors Fail To Capture The High Degree Of Variance In Fatigue Life Caused By Minor Manufacturing Deviations And Stochastic Operational Loads. The Sensitivity Analysis Underscored The Extreme Criticality Of Strictly Controlling Both The Reinforcement Winding Angle During Production And The Amplitude Of Transient Pressure Surges During Operation To Ensure Long-Term Structural Integrity.

5.2 Future Directions For Pipeline Engineering

The Findings Presented In This Study Provide A Critical Foundation For Advancing The Design, Manufacturing, And Lifecycle Management Of Flexible Pipeline Infrastructure. As The Global Energy Industry Pushes Toward Deeper Subsea Developments And The Transportation Of Novel Energetic Fluids Such As Pressurized Hydrogen Gas, The Structural Demands On Reinforced Thermoplastic Pipes Will Only Intensify. Future Engineering Efforts Must Focus On Developing Advanced, Functionally Graded Reinforcement Architectures Capable Of Dynamically Adapting To Complex Multiaxial Stress States Without Experiencing Severe Internal Stress Concentrations. Furthermore, The Integration Of Advanced Smart Sensing Technologies Directly Into The Composite Pipe Wall, Such As Distributed Fiber Optic Strain Sensors, Will Enable Real-Time Structural Health Monitoring. By Coupling Continuous Operational Data With The Probabilistic Reliability Models Developed Herein, Operators Can Transition From Schedule-Based Maintenance To Dynamic, Predictive Lifecycle Management, Maximizing The Utility Of The Infrastructure While Strictly Minimizing The Risk Of Catastrophic Environmental Failure. Ultimately, The Continuous Refinement Of Multiaxial Damage Models And Probabilistic Assessment Tools Remains Paramount To Ensuring The Sustainable And Safe Expansion Of Global Flexible Pipeline Networks.

References

- Yao, Jingyu, Et Al. "Explainable Ai Enhanced Traffic Forecasting For Proactive Autonomous Vehicle Routing." 2026 Ieee Conference On Technologies For Sustainability (Sustech). Ieee, 2026.
- Yang, Z., Hu, D., Guo, Q., Zuo, L., & Ji, W. (2023). Visual E 2 C: Ai-Driven Visual End-Edge-Cloud Architecture For 6g In Low-Carbon Smart Cities. *Ieee Wireless Communications*, 30(3), 204-210.
- Wang, J. (2026). A Comparative Conceptual Analysis Of Co2 Heat Pump Dryers With Closed-Loop And Open-Loop Air Cycles. *Energy Conversion And Management*, 352, 121093.
- Wang, J., & Lu, W. (2025). A Streamlined Polynomial Regression-Based Modeling Of Speed-Driven Hermetic-Reciprocating Compressors. *Applied Sciences*, 15(22), 12016.
- Yang, Y., Ma, X., Li, C., Zheng, Z., Zhang, Q., Huang, G., ... & Zhao, Q. (2021). Believe What You See: Implicit Constraint Approach For Offline Multi-Agent Reinforcement Learning. *Advances In Neural Information Processing Systems*, 34, 10299-10312.
- Chen, B. L., Zhang, J. Y., Xu, W. J., Yan, S. Y., & Zhu, X. Q. (2025). Thermodynamic And Kinetic Studies Of Mononuclear Non-Heme High-Valent (Feo) 2+ Complexes. *Acs Omega*, 10 (4), 3718.

- Chen, Z. Y., Zhang, J. P., Hu, S. S., Zhang, K. X., Li, Y. Z., Wang, H. C., ... & Dudley, M. (2026, June). Investigation Of Spoke Pattern Of Stacking Faults In 4h-Sic Wafers Grown By Physical Vapor Transport Method. In *Materials Science Forum* (Vol. 1190, Pp. 55-62). Trans Tech Publications Ltd.
- Ma, Y., & Qu, D. (2026). Machine Learning Based Markov Decision Framework For Optimizing Circular Economy Systems. *Engineering Proceedings*, 120(1), 44.
- Hu S, Chen Z, Zhang K, Et Al. Stacking Fault Analysis For The Early-Stages Of Pvt Growth Of 4h-Sic Crystals[J]. *Journal Of Crystal Growth*, 2026, 681: 128523.
- Wang, Y. Y., Lou, M., Wang, Y., Wu, W. G., & Yang, F. (2022). Stochastic Failure Analysis Of Reinforced Thermoplastic Pipes Under Axial Loading And Internal Pressure. *China Ocean Engineering*, 36(4), 614-628.
- Wan, H., Cheng, J., Deng, Y., Wu, D., Chen, Y., Lin, Z., ... & Ji, X. Towards Physics Aware Embodied Control With Graph Based Object-Centric Learning. *Acm Transactions On Cyber-Physical Systems*.
- Luan, S., Tang, M., Mu, H., Yu, J., Wang, P., & Zhang, L. (2025). A Co-Precipitation Route To Produce Batio3 Nanopowders With High Tetragonality For Ultra-Thin Mlccs Application. *Journal Of Materials Science: Materials In Electronics*, 36 (9), 526.
- Chen, B. L., Jing, S., & Zhu, X. Q. (2023). Thermodynamics Evaluation Of Selective Hydride Reduction For A, B-Unsaturated Carbonyl Compounds. *Molecules*, 28 (6), 2862.
- Zhang, K. X., Chen, Z. Y., Hu, S. S., Zhang, J. P., Li, Y. Z., Wu, D. L., ... & Soukhojak, A. (2026, August). Observation And Analysis Of The “Galaxy” Defect In 4h-Sic Through X-Ray Synchrotron Topography. In *Defect And Diffusion Forum* (Vol. 452, Pp. 73-78). Trans Tech Publications Ltd.
- Zhu, Q., & Chen, H. (2025, August). Bias Correction Of Wind Forecasts From The Noaa Global Ensemble Forecast System (Gefs) Using Machine Learning. In *Igarss 2025-2025 Ieee International Geoscience And Remote Sensing Symposium* (Pp. 4637-4640). Ieee.
- Chen, B., Hu, X., & Zhu, X. (2023). Essential Rule Derived From Thermodynamics And Kinetics Studies Of Benzopyran Compounds. *Molecules*, 28(24), 8039.
- Li, Y. Z., Zhang, J. P., Chen, Z. Y., Wang, H. C., Zhang, K. X., Hu, S. S., ... & Dudley, M. (2026, August). Growth And Characterization Of High-Quality Thick Epitaxial 4h-Sic Wafers For High Voltage Devices. In *Defect And Diffusion Forum* (Vol. 452, Pp. 79-85). Trans Tech Publications Ltd.
- Luan, S., Si, S., Zhang, L., Wang, P., Jian, G., Yang, J.,... & Cao, X. (2023). Fabrication Of Batio3 Nanopowders With High Tetragonality Via Two-Step Assisted Rotary Furnace Calcination For Mlcc Applications. *Ceramics International*, 49 (8), 12529-12539.
- Wang, X., Wang, P., Jiang, W., Wu, F., Kiani, M., & Arefi, M. (2021). Mathematical And Computer Simulation For Electro-Magneto-Thermo-Elastic Buckling Of The Porous Nano System. *Structural Engineering And Mechanics*, 80(2), 231-242.
- Li, X., Wang, P., Li, G., & Zhang, Y. (2023). Design Of A Novel Self-Test-On-Chip Interface Asic For Capacitive Accelerometers. *Ieee Transactions On Circuits And Systems I: Regular Papers*, 70(7), 2834-2843.
- Yang, Y., Hu, H., Li, W., Li, S., Yang, J., Zhao, Q., & Zhang, C. (2023, June). Flow To Control: Offline Reinforcement Learning With Lossless Primitive Discovery. In *Proceedings Of The Aaai Conference On Artificial Intelligence* (Vol. 37, No. 9, Pp. 10843-10851).
- Wang, Y., Lou, M., Liang, W., & Zhang, C. (2023). Numerical And Experimental Investigation On Tensile Fatigue Performance Of Reinforced Thermoplastic Pipes. *Ocean Engineering*, 287, 115814.

- Chen, B. L., Yan, S. Y., & Zhu, X. Q. (2023). A Mechanism Study Of Redox Reactions Of The Ruthenium-Oxo-Polypyridyl Complex. *Molecules*, 28(11), 4401.
- Liu, J., & Huang, Y. (2026). Gbmp-Lca: A Gradient Boosting–Based Framework For Performance Prediction And Life-Cycle Optimization Of Green Building Materials. *Fundamental Scientific Reports In Multidisciplinary Areas*, 2 (02), 193-204.
- Li, H., Zheng, T., Peng, Y., & Boudagher-Fadel, M. K. (2023). The Fusulinids In A Middle-Late Permian Carbonate Platform (From Maokou To Wuchiapingian Stage) In Eastern Sichuan Basin, China. In *Stratigraphy & Timescales* (Vol. 8, Pp. 413-435). Academic Press.
- Yang, Y., Wang, Q., Li, C., Hu, H., Wu, C., Jiang, Y., ... & Xu, B. (2025, May). Fewer May Be Better: Enhancing Offline Reinforcement Learning With Reduced Dataset. In *International Conference On Learning Representations* (Vol. 2025, Pp. 7076-7098).
- Li, J., Luo, Y., & Ling, Y. (2026). Carbon-Aware Reinforcement Learning For Cost-Optimal Energy Management Of Hydrogen-Electric Heavy-Duty Trucks. *Strategic Management Insights*, 3 (2), 1-10.
- Lv, X., Liu, S., Wang, P., Mohammad-Rezaei Bidgoli, E., & Arefi, M. (2023). On The Dynamics And Wave Propagation Of Reinforced Composite Nanosystem. *Engineering With Computers*, 39(1), 151-171.
- Xiong, S., Chen, T., Rupendra, A., Clement, C., Gasparri, E., & Lucchi, E. (2026). Embodied Carbon Of Progressive Timber Integration In A 47-Storey Tropical High-Rise: A Singapore Public Housing Case Study. *Building And Environment*, 114910.
- Peng, Y., Li, H., Boudagher-Fadel, M., Wang, L., Zhang, D., Zheng, T., & Yang, K. (2022). Benthic Foraminifera Distribution And Sedimentary Environmental Evolution Of A Carbonate Platform: A Case Study Of The Guadalupian (Middle Permian) In Eastern Sichuan Basin. *Marine Micropaleontology*, 170, 102079.
- Zhou, X., Wang, P., Al-Dhaifallah, M., Rawa, M., & Khadimallah, M. A. (2022). A Machine Learning-Based Model For The Estimation Of The Critical Thermo-Electrical Responses Of The Sandwich Structure With Magneto-Electro-Elastic Face Sheet. *Advances In Nano Research*, 12(1), 81-99.
- Lu, J., Fang, Y., Yang, X., Hu, W., Tuo, J., & Zhang, F. (2025). Modal Metamodeling-Based Uncertainty Propagation For Frequency Response In Non-Proportional Damping Systems. *International Journal Of Structural Stability And Dynamics*, 2650279.
- Luan, S., Wang, P., Zhang, L., He, Y., Huang, X., Jian, G.,... & Fu, Z. (2023). Atmospherically Hydrothermal Assisted Solid-State Reaction Synthesis Of Ultrafine Batio3 Powder With High Tetragonality. *Journal Of Electroceramics*, 50 (4), 97-111.
- Pabon, J. J. G., Wang, J., Chamanehpour, E., Salami, D., & Khosravi, A. (2025). Dynamic Integration Of Solar-Powered Hydrogen Systems With Fuel Cells And District Heating For Green Data Centers. *International Journal Of Hydrogen Energy*, 196, 152557.