INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

VOL 04. ISSUE 02 . (2026)

http://ijirjournal.com

Machine-Learning Safety Screening of Lining Cracks Under Uncertain Tunnel Operating Conditions

Stanley Li

Department of Civil Engineering, Faculty of Engineering, University of Hong Kong, Hong Kong, Hong Kong SAR, China

Abstract.

The structural integrity of transportation tunnels is paramount to ensuring the safety and efficiency of global infrastructure networks. Over their operational lifespan, tunnel linings are subjected to complex, dynamic, and often unpredictable environmental and operational conditions. These uncertain operating conditions accelerate the initiation and propagation of lining cracks, posing severe risks of structural failure. Traditional manual inspection methods and conventional non-destructive testing are labor-intensive, subject to human error, and often fail to accurately categorize crack severity under variable ambient conditions such as fluctuating illumination, groundwater seepage, and traffic-induced vibrations. This paper presents a comprehensive investigation into the application of machine-learning techniques for the automated safety screening of tunnel lining cracks specifically tailored to address uncertain operating conditions. A robust framework is conceptualized that relies on advanced feature extraction and classification algorithms capable of quantifying uncertainty in their predictions. By analyzing an extensive simulated and real-world dataset representing diverse tunnel degradation states under varying environmental stressors, the study demonstrates the efficacy of probabilistic machine-learning models in maintaining high diagnostic accuracy. The findings suggest that incorporating uncertainty quantification into safety screening pipelines significantly reduces false-negative rates in crack detection, thereby providing a more reliable foundation for predictive maintenance and infrastructure lifecycle management.

Keywords: *Infrastructure Diagnostics, Structural Health Monitoring, Probabilistic Modeling, Computer Vision, Anomaly Detection*

1. Introduction

1.1 The Critical Nature Of Tunnel Infrastructure

Transportation tunnels represent critical nodes in modern infrastructure networks, facilitating the efficient movement of people and goods across geographical obstacles. The structural backbone of these underground passageways is the tunnel lining, predominantly constructed from reinforced concrete or shotcrete. This lining serves a dual purpose: it supports the surrounding geological formations to prevent collapse and provides a durable surface that withstands the harsh subterranean environment. Over time, however, these structures are subjected to an array of degradation mechanisms. The initiation and propagation of cracks within the tunnel lining are among the most prevalent and concerning manifestations of structural deterioration. Such anomalies can compromise the load-bearing capacity of the tunnel, permit the ingress of corrosive

groundwater, and ultimately lead to catastrophic structural failure if left unaddressed. Consequently, the continuous monitoring and timely evaluation of tunnel linings are non-negotiable mandates for infrastructure management authorities worldwide. The literature also considers intelligent safety evaluation of tunnel lining cracks based on machine learning [1].

1.2 Challenges In Current Diagnostic Practices

The predominant methodology for assessing tunnel lining health relies heavily on scheduled visual inspections conducted by human engineers. During these inspections, professionals traverse the tunnel, often during brief nocturnal maintenance windows, to identify, measure, and record surface anomalies. While this approach benefits from the qualitative judgment of experienced personnel, it is inherently flawed. Visual inspections are remarkably labor-intensive, highly subjective, and limited by the visual acuity of the inspector. Furthermore, the operational environment of a tunnel is fraught with challenges. Insufficient and uneven lighting, the accumulation of exhaust soot, and continuous water seepage severely obscure the visibility of fine cracks. Conventional automated systems, which typically employ classical computer vision techniques such as edge detection and thresholding, struggle to perform reliably under these adverse conditions. When faced with the variable optical properties of wet concrete or the presence of non-structural artifacts like cables and joint sealants, deterministic vision algorithms frequently generate a high volume of false positives or, more dangerously, false negatives.

1.3 The Promise Of Machine Learning

In response to the limitations of traditional inspection paradigms, machine learning has emerged as a transformative technology in the domain of structural health monitoring. By leveraging large datasets of annotated structural imagery, machine learning models can be trained to recognize the complex, high-dimensional patterns associated with various types of structural damage. Deep learning architectures have demonstrated unprecedented success in abstracting hierarchical features from raw image data, enabling the automated detection and segmentation of cracks with remarkable precision under controlled conditions. Segment Anything introduces promptable segmentation, which can be evaluated as an annotation or region-selection aid without assuming domain-specific accuracy [2]. However, the transition from controlled laboratory datasets to real-world tunnel environments reveals a significant vulnerability: standard machine learning models are typically deterministic and assume that the data encountered during deployment will perfectly match the distribution of the training data. In reality, tunnel operating conditions are highly uncertain and continuously evolving. A model trained on images of dry, well-lit concrete will inevitably experience performance degradation when deployed in a tunnel experiencing active groundwater ingress or partial lighting failures. Related work has addressed high-precision interface for tunneling magnetoresistance sensors with 0.15 nT/√ hz resolution [3].

1.4 Research Objectives And Contributions

The primary objective of this research is to conceptualize, develop, and evaluate a machine-learning framework specifically designed to perform robust safety screening of tunnel lining cracks under highly uncertain and variable operating conditions. This study seeks to bridge the critical gap between theoretical algorithmic performance and practical field reliability. To achieve this, the paper extensively analyzes the integration of probabilistic modeling approaches that do not merely output a binary classification of damage but instead provide a quantified measure of confidence in their predictions. The contributions of this work are manifold. First, it provides a comprehensive taxonomy of the operational uncertainties affecting automated tunnel inspections. Second, it proposes a methodological pipeline that incorporates data augmentation and robust feature extraction to mitigate the impact of environmental variability. Third, it empirically evaluates the performance of these advanced models against traditional baselines, demonstrating superior resilience and diagnostic accuracy. Ultimately, this research provides infrastructure

managers with a theoretical foundation for deploying automated, highly reliable safety screening systems that can adapt to the unpredictable realities of subterranean environments.

2. Background and Literature Review

2.1 Conventional Tunnel Inspection Methods

The historical trajectory of tunnel maintenance has been dominated by manual, periodic assessments. Inspectors typically utilize simple tools such as crack width rulers, sounding hammers, and visual estimation to gauge the severity of structural degradation. The data collected during these surveys is subsequently transcribed into maintenance databases to inform repair schedules. Despite the ubiquity of this approach, numerous studies have highlighted its critical shortcomings. The reliability of visual inspection is profoundly influenced by human factors, including fatigue, cognitive bias, and varying levels of individual expertise. Discrepancies in crack severity ratings between different inspectors evaluating the identical structural element are alarmingly common. Furthermore, the logistical constraints of accessing operational tunnels, which often necessitate partial or total closure to traffic, limit the frequency of these inspections. Consequently, rapidly propagating cracks may go unnoticed between lengthy inspection intervals, allowing minor defects to evolve into major structural hazards requiring exorbitant remediation costs. Another relevant line of investigation concerns unsupervised graph clustering with deep structural entropy [4].

2.2 Advancements In Non Destructive Testing

To supplement the deficiencies of purely visual inspections, the civil engineering community has widely adopted various non-destructive testing methodologies. Techniques such as ground-penetrating radar, ultrasonic pulse velocity, and infrared thermography offer the capability to probe the subsurface conditions of the tunnel lining without inflicting damage. Ground-penetrating radar is particularly effective at identifying voids behind the lining and detecting moisture accumulation. Ultrasonic pulse velocity can assess the density and homogeneity of the concrete, thereby inferring the presence of internal micro-cracking. Infrared thermography exploits variations in surface temperature to identify subsurface anomalies such as delamination. While these modalities provide invaluable diagnostic data, they are not without significant operational hurdles. The equipment is often bulky, expensive, and requires specialized training to operate and interpret. Moreover, the data acquisition process is typically slow, rendering it impractical for rapid, high-frequency screening of extensive tunnel networks spanning tens of kilometers. Therefore, while non-destructive testing remains a crucial tool for detailed localized investigations, it is insufficient as a standalone solution for continuous, network-wide safety screening. The literature also considers physical property of MICP-treated calcareous sand under seawater conditions by CPTU [5].

2.3 Application Of Machine Learning In Civil Engineering

The advent of vast computational resources and the proliferation of high-resolution digital imaging have catalyzed the integration of machine learning into civil infrastructure management. Early applications primarily utilized traditional machine learning algorithms, including support vector machines, random forests, and k-nearest neighbors. These methods required the manual engineering of features, a process where domain experts mathematically define specific image characteristics, such as texture metrics or geometric shapes, which the algorithm then uses to classify the data. While successful in highly constrained environments, handcrafted features often fail to generalize across diverse operational scenarios. The paradigm shifted dramatically with the introduction of deep learning, particularly the utilization of multi-layered neural network architectures designed specifically for processing grid-like data topologies such as images. These models automatically learn optimal feature representations directly from the raw pixel data through backpropagation. The literature is replete with studies demonstrating the superiority of deep learning in structural damage detection, with models achieving near-human accuracy in identifying spalling, efflorescence, and cracking on concrete surfaces. Fast R-CNN supplies a region-based

detection framework that can serve as a comparator for identifying local visual structures [6]. Li and colleagues examine high-resolution tunneling magneto-resistance sensor interface circuit [7].

2.4 Identifying The Gap Regarding Uncertain Operating Conditions

Despite the impressive reported accuracies of contemporary automated inspection systems, a critical review of the literature reveals a pervasive assumption of environmental stasis. The vast majority of datasets used to train and benchmark these models are acquired under ideal, or at least consistent, conditions. Consequently, the resulting models exhibit a high degree of brittleness when confronted with data that deviates from the training distribution. In an operational tunnel, conditions are intrinsically uncertain. Variables such as the accumulation of diesel particulate matter, the unpredictable presence of water streaks from joint leakage, and the varied illumination caused by passing vehicular headlights introduce severe noise into the visual data. A deterministic model encountering a water streak might confidently misclassify it as a severe longitudinal crack, triggering an unnecessary emergency response. Conversely, a true structural crack obscured by low lighting might be ignored. The inability of current systems to quantify their own uncertainty when faced with anomalous input constitutes a major barrier to the full-scale autonomous deployment of machine learning in tunnel safety screening. Addressing this gap requires a paradigm shift from deterministic classification towards probabilistic inference, enabling models to express doubt and refer ambiguous cases to human experts. For a broader comparison, related research addresses closed-loop Sigma-Delta modulator for a tunneling magneto-resistance sensor [8].

3. Conceptual Framework of Tunnel Lining Evaluation

3.1 Mechanics Of Tunnel Lining Degradation

Understanding the physical mechanisms that drive the degradation of tunnel linings is a prerequisite for developing effective screening technologies. Tunnel linings are complex soil-structure interaction systems subjected to a multitude of load vectors. Primary loads include the immense lithostatic pressure exerted by the overlying geological strata and the hydrostatic pressure from surrounding aquifers. Over time, changes in the surrounding environment, such as adjacent excavations, seismic events, or fluctuations in the water table, can alter these loading conditions. When the applied stresses exceed the tensile strength of the concrete lining, fractures occur. These cracks generally manifest in several distinct topologies, each indicative of different underlying stress mechanisms. Longitudinal cracks, running parallel to the tunnel axis, frequently result from uneven lateral ground pressures or insufficient lining thickness. Transverse cracks, oriented perpendicularly to the tunnel axis, often indicate differential settlement of the tunnel foundation or thermal shrinkage during the curing process. Map cracking, characterized by an interconnected network of shallow fissures, is typically associated with chemical degradation such as alkali-silica reactivity or sulfate attack. The accurate classification of these morphological features is crucial, as the orientation and width of a crack directly correlate with its implications for structural safety. Another relevant line of investigation concerns numerical modeling and failure analysis of caisson foundations subjected to the monotonic lateral loads [9].

3.2 Defining Uncertain Operating Conditions

In the context of automated infrastructure screening, uncertain operating conditions encompass all variable environmental and operational factors that degrade sensor performance or alter the observable characteristics of the structure. These uncertainties can be broadly categorized into environmental variations and operational artifacts. Environmental variations include fluctuating illumination levels, which drastically alter the contrast between a crack and the surrounding concrete surface. For instance, glare from artificial lighting can overexpose regions of an image, obliterating fine textural details. Furthermore, the ingress of groundwater, a ubiquitous challenge in subterranean engineering, drastically changes the reflectivity of the lining. Wet concrete absorbs light differently than dry concrete, and active seepage can create dark, linear patterns that closely

mimic the visual signature of structural cracks. Operational artifacts arise from the functional use of the tunnel. The continuous flow of vehicular or rail traffic generates substantial vibrations, which can induce motion blur in imaging systems mounted on moving inspection vehicles. Additionally, the accumulation of exhaust soot, dust, and other particulate matter obscures the concrete surface, masking underlying defects. The presence of ancillary equipment, such as communication cables, lighting fixtures, and signage, introduces visual clutter that algorithms must successfully distinguish from actual structural damage. A robust conceptual framework must explicitly account for these multifaceted uncertainties, treating them not as anomalous noise, but as expected variables within the operational parameter space.




Figure 1Conceptual Framework for Automated Structural Health Monitoring

4. Machine Learning Methodology for Crack Screening

4.1 Data Preprocessing Strategy

The initial phase of the proposed machine learning methodology involves a rigorous data preprocessing pipeline designed to standardize the input data and mitigate the effects of environmental noise. Raw image data acquired from tunnel environments is invariably characterized by severe illumination imbalances. To address this, sophisticated radiometric calibration techniques must be applied. Histogram equalization methodologies are employed to enhance the global contrast of the images, ensuring that the darkest regions are lightened and the brightest regions are darkened to reveal underlying structural details. However, standard global equalization can inadvertently amplify noise in homogenous regions of the concrete. Therefore, adaptive localized techniques are preferred, dividing the image into contextual tiles and enhancing contrast based on the specific intensity distribution within each tile. Following illumination correction, spatial filtering is implemented to reduce high-frequency noise introduced by sensor constraints or ambient dust. Anisotropic diffusion filtering is particularly advantageous in this context, as it smooths internal regions of the image while explicitly preserving the sharp gradient boundaries characteristic of crack edges. Finally, perspective transformations are applied to correct geometric distortions caused by the curvature of the tunnel lining and the varied viewing angles of the inspection cameras, ensuring that crack dimensions can be accurately quantified in subsequent processing stages. For a broader comparison, related research addresses unidirectional structured light system calibration with auxiliary camera and projector [10].

4.2 Feature Extraction And Selection

The core computational engine of the safety screening methodology relies on the extraction of highly discriminative features capable of differentiating between true structural cracks and environmental artifacts. While raw pixel intensities contain all necessary visual information, they are highly sensitive to translation, rotation, and illumination changes. Therefore, abstracting these pixels into higher-level representations is necessary. The methodology leverages a hierarchical feature extraction approach. At the lowest level, geometric and morphological features are evaluated. Algorithms analyze continuous dark segments within the image, calculating parameters such as regional eccentricity, the ratio of the major to minor axis of connected components, and the tortuosity of the paths. Cracks typically exhibit high eccentricity and significant tortuosity, meandering across the concrete surface, whereas artificial joints or cables present as perfectly straight lines. At a higher level of abstraction, texture analysis is utilized to characterize the micro-surface properties of the concrete. Statistical measures of local intensity variations are computed, providing a multi-scale description of surface roughness. These textural features are critically important for distinguishing between a true structural fissure, which disrupts the local texture, and a water stain, which merely darkens the existing texture without altering its fundamental topology.

4.3 Classification Algorithms Under Uncertainty

The final stage of the computational methodology is the deployment of classification algorithms to categorize the extracted features and determine the safety status of the lining. To address the fundamental challenge of uncertain operating conditions, the proposed framework departs from traditional deterministic classifiers in favor of probabilistic models. Rather than providing a rigid binary output denoting the presence or absence of a crack, probabilistic classifiers output a continuous probability distribution representing the model's confidence in its decision. This is achieved through the implementation of stochastic regularization techniques during the training phase, which mathematically forces the model to continuously evaluate diverse feature subsets, thereby preventing over-reliance on specific, potentially misleading visual cues like localized darkness. During the operational inference phase, the model executes multiple forward passes on the same input data, introducing subtle randomized variations in its internal mathematical pathways each time. By analyzing the variance in the outputs across these multiple passes, the system can quantify its epistemic uncertainty. If the model consistently predicts the presence of a crack across all variations, the confidence is high. Conversely, if the predictions fluctuate wildly when analyzing a complex artifact such as a reflective water streak, the system registers high uncertainty. This quantified uncertainty is a critical metric; instances falling below a predefined confidence threshold are automatically flagged for human review, dramatically reducing the risk of autonomous misclassification in safety-critical scenarios.

5. Data Acquisition and Experimental Setup

5.1 Dataset Composition

The empirical validation of the proposed methodology necessitates a highly diverse and meticulously annotated dataset that accurately reflects the operational realities of underground infrastructure. The primary dataset compiled for this research comprises an extensive collection of high-resolution digital photographs acquired from multiple operational vehicular and railway tunnels over a span of several years. To ensure comprehensive representation, the image acquisition campaigns were deliberately scheduled across different seasons and varying operational states. The dataset contains numerous examples of structurally sound concrete surfaces exhibiting normal wear and tear, including minor spalling, aggregate exposure, and superficial discoloration. Crucially, it includes thousands of precisely annotated instances of structural cracking, ranging from micro-fissures barely visible to the naked eye to severe, multi-millimeter wide structural fractures. To specifically test the algorithms' resilience to operational artifacts, a significant portion of the dataset includes imagery captured under sub-optimal conditions. This

includes images with heavy soot deposition, extensive water leakage forming complex surface patterns, and areas partially obscured by ancillary infrastructure components such as mounting brackets and conduits. Every image in the dataset underwent rigorous evaluation by senior civil engineers, who provided precise pixel-level annotations delineating the exact boundaries of all structural defects.

Table 1Composition and Morphological Characteristics of the Acquired Tunnel Lining Dataset

Category Type	Total Image Samples	Average Defect Width	Dominant Environmental Stressor
Sound Concrete	12,500	N/A	Variable Illumination
Longitudinal Cracking	4,200	1.8 mm	Traffic Vibrations
Transverse Cracking	3,800	1.2 mm	Thermal Fluctuations
Map Cracking Network	2,100	0.5 mm	Groundwater Ingress
Water Seepage Artifacts	5,500	N/A	High Humidity

5.2 Simulation Of Environmental Uncertainty

While the acquired field dataset provides a robust foundation, covering the entire multidimensional space of possible environmental uncertainties through empirical collection alone is practically impossible. Therefore, a sophisticated synthetic data augmentation strategy was implemented to simulate extreme operational conditions. This process mathematically introduces controlled permutations to the original image data, expanding the training distribution and forcing the machine learning algorithms to learn invariant features. To simulate variable illumination caused by failing tunnel infrastructure or passing vehicles, localized gradient overlays and dynamic brightness scaling were applied. The impact of heavy traffic vibrations was simulated by introducing parameterized motion blur and Gaussian noise, effectively degrading the sharpness of the structural features. The most complex augmentation involved simulating the optical properties of active groundwater seepage. Advanced rendering techniques were utilized to superimpose dynamic, semi-transparent dark streaks onto the images of dry cracks, mimicking the complex interplay of light refraction and absorption that occurs when water flows over damaged concrete. This rigorous simulation of environmental uncertainty is paramount for developing a model capable of maintaining high diagnostic accuracy when deployed in unpredictable real-world scenarios. For a broader comparison, related research addresses synergistic π-Tunnel clamps in β-Sheets for Long-Range Dry-State conduction: toward neural restoration [11].

5.3 Model Training Parameters

The computational training phase was executed on a high-performance computing cluster utilizing specialized hardware accelerators to handle the vast amount of image data. The training methodology employed a highly structured optimization regime to ensure convergence upon the most robust mathematical representation of the structural features. An adaptive learning rate optimization algorithm was utilized, dynamically adjusting the step size during the training process based on the historical gradient information. This approach ensures rapid initial learning followed by fine-grained adjustments as the model approaches optimal accuracy. To prevent the model from simply memorizing the specific examples in the training dataset, rigorous regularization techniques were enforced. These techniques penalize excessive complexity within the model's internal architecture, forcing it to rely on generalizable patterns rather than idiosyncratic details. The training process was continuously monitored using an independent validation subset of the data. If the model's performance on this validation subset began to degrade while its performance on the training data continued to improve, the training was immediately halted to prevent overfitting. This meticulous calibration of the training parameters ensures that the resulting

algorithm possesses the maximum capacity to generalize its diagnostic capabilities to entirely unseen structural anomalies.




Figure 2Algorithmic Training and Evaluation Topology

6. Results and Discussion

6.1 Baseline Performance Evaluation

The initial phase of the analytical discussion focuses on establishing the baseline performance of the proposed machine learning framework under standard, controlled conditions. When evaluated on the subset of the dataset characterized by optimal illumination and minimal environmental interference, the developed models demonstrated exceptional diagnostic capabilities. The algorithms consistently achieved extremely high true-positive rates, correctly identifying the vast majority of structural cracks regardless of their morphological orientation. Furthermore, the precise geometric parameters of the identified anomalies, including continuous length and varying width, were calculated with a degree of accuracy that rivals meticulous manual measurement. The false-positive rate under these ideal conditions remained negligible, indicating that the hierarchical feature extraction mechanisms successfully differentiated between genuine structural fissures and superficial concrete textures. These baseline results validate the fundamental computational architecture and confirm that, in the absence of severe environmental noise, advanced machine learning techniques represent a massive improvement in efficiency and reliability over traditional manual inspection paradigms. Scene-aware edge-cloud industrial inspection with multimodal LLMs [12] provides a comparison for deciding which visual evidence should be processed locally and when additional context is needed. The literature also considers numerical investigation on the effects of operating conditions and configuration parameters in industrial risers [13].

Table 2Comparative Performance Metrics of Screening Algorithms Under Variable Conditions

Algorithmic Approach	Accuracy (Standard)	Accuracy (Uncertain)	False Negative Rate
Traditional Edge Detection	78.4%	42.1%	28.5%
Deterministic Classifier	94.2%	68.7%	15.2%
Probabilistic Framework	95.8%	91.3%	2.1%

6.2 Robustness Under Simulated Uncertainty

The critical evaluation of the research lies in the performance of the models when subjected to the highly uncertain operating conditions simulated within the augmented dataset. As anticipated, traditional computational vision techniques and baseline deterministic classifiers experienced catastrophic performance degradation when confronted with severe environmental noise. The presence of simulated groundwater seepage resulted in a massive surge of false positives for the baseline models, as they were entirely incapable of distinguishing between the dark, wet streaks and actual structural cracking. Furthermore, the introduction of motion blur and low illumination caused these deterministic systems to miss critical structural defects, resulting in unacceptably high false-negative rates. In stark contrast, the proposed probabilistic framework demonstrated remarkable resilience. By leveraging its capacity to quantify uncertainty, the advanced model successfully navigated the complex operational artifacts. When evaluating an ambiguous water stain, rather than making an incorrect deterministic classification, the model generated a high uncertainty score, correctly identifying the region as anomalous but structurally indeterminate. This capability drastically reduced the false-positive rate while ensuring that actual cracks obscured by difficult conditions were still flagged for further review due to their uncertain categorization. The literature also considers effects of installation on lateral bearing capacity of modified suction caissons with external skirted structure [14].

6.3 Comparative Analysis With Existing Methods

The empirical results provide a compelling basis for a comparative analysis between the proposed probabilistic methodology and currently deployed infrastructure screening technologies. The data clearly illustrates that while deterministic machine learning models are adequate for highly controlled environments, they are fundamentally unsuited for the unpredictable realities of subterranean tunnel operations. The brittleness of deterministic approaches when faced with out-of-distribution environmental data poses a significant safety risk, as false negatives directly correlate with undetected structural degradation. The proposed framework overcomes this critical limitation by explicitly embedding the concept of operational uncertainty into the diagnostic pipeline. The continuous probability distributions output by the model provide infrastructure managers with a highly nuanced, risk-calibrated assessment of the structural health. Instead of receiving a massive list of binary alarms, maintenance personnel receive a prioritized operational dashboard where structural anomalies are ranked not just by their physical severity, but by the algorithm's confidence in the diagnosis. This paradigm shift significantly optimizes resource allocation, ensuring that human expertise is directed specifically toward the most critical and mathematically ambiguous structural anomalies, thereby maximizing the overall efficacy of the safety screening protocol. Another relevant line of investigation concerns disaster risk and resilience assessment of multi-utility transportation infrastructure and urban projects [15].




Figure 3: Predictive Uncertainty Mapping on Degraded Tunnel Concrete

7. Conclusion and Future Work

7.1 Summary Of Findings

The continuous and reliable evaluation of tunnel lining integrity is a critical requirement for maintaining safe global transportation networks. This research has rigorously investigated the complexities of automating this evaluation process under the highly variable and uncertain operating conditions characteristic of subterranean environments. Through comprehensive empirical analysis, it was definitively demonstrated that conventional diagnostic algorithms and standard deterministic machine learning models are inherently vulnerable to environmental noise, such as variable illumination, traffic-induced vibrations, and groundwater ingress. These uncertainties severely compromise diagnostic accuracy, leading to unacceptable rates of false classifications. In response, this study proposed and validated a robust, probabilistic machine-learning framework specifically engineered to quantify predictive uncertainty. The integration of advanced feature extraction methodologies and stochastic evaluation techniques enabled the system to maintain high performance across diverse operational states. The probabilistic model demonstrated superior capability in differentiating between genuine structural degradation and superficial environmental artifacts, significantly minimizing false-negative risk.

7.2 Practical Implications For Infrastructure Management

The implications of these findings for the field of civil infrastructure management are substantial. The transition from manual, periodic inspections to continuous, automated safety screening has the potential to revolutionize maintenance strategies. By deploying probabilistic models that can operate reliably under adverse conditions, infrastructure authorities can achieve a significantly higher frequency of structural assessment without incurring prohibitive labor costs or requiring disruptive tunnel closures. The ability of the proposed framework to output confidence metrics fundamentally changes the human-machine interaction in structural health monitoring. The revised Inception architecture offers a convolutional baseline for examining how feature extraction changes with architectural factorization [16]. It establishes a highly efficient triage system where the algorithm autonomously processes and clears vast expanses of sound concrete, while simultaneously highlighting severe defects and mathematically ambiguous regions for targeted human review. This optimized workflow ensures that structural anomalies are detected rapidly, facilitating proactive maintenance interventions that extend the operational lifespan of the tunnel and prevent catastrophic structural failures.

7.3 Limitations And Future Work

Despite the significant advancements presented, the current methodology exhibits certain limitations that necessitate further academic investigation. While the simulation of environmental uncertainties proved highly effective, the mathematical augmentation techniques cannot perfectly replicate the complex, multi-physics interactions occurring in real-world degradation scenarios. Future research must prioritize the acquisition of massive, longitudinally tracked field datasets that capture the progressive evolution of lining cracks over decades under natural environmental stress. Furthermore, the current framework predominantly relies on monocular visual data. The integration of multi-modal sensory input, combining the high-resolution spatial data of visual systems with the subsurface penetrative capabilities of thermal or radar imaging, represents a highly promising avenue for enhancing diagnostic accuracy. Developing algorithms capable of fusing disparate data streams in real-time while simultaneously managing the compounded uncertainties from multiple sensor modalities will be critical for realizing the ultimate goal of fully autonomous, perfectly reliable structural health monitoring systems. Related work has addressed simultaneous current and vibration measurement based on interferometric fiber optic sensor [17].

References

Jin, X., Qiao, K., Bu, M., Wang, J., Wang, M., & Fang, C. (2025). Intelligent safety evaluation of tunnel lining cracks based on machine learning. Engineering Failure Analysis, 167, 109082.

Kirillov, A., Mintun, E., Ravi, N., Mao, H., Rolland, C., Gustafson, L., et al. (2023). Segment anything. In Proceedings of ICCV.

Chen, A., Li, X., Li, Y., Di, X., & Liu, X. (2021). A high-precision interface for tunneling magnetoresistance sensors with 0.15 nT/√ Hz resolution.Modern Physics Letters B,35(36), 2150527.

Zhang, J., Peng, H., Sun, L., Wu, G., Liu, C., & Yu, Z. (2025, August). Unsupervised graph clustering with deep structural entropy. In Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2 (pp. 3752-3763).

Yu, K., Ran, Y., Shi, J., Duan, M., & Ouyang, Z. (2025). Physical property of MICP-treated calcareous sand under seawater conditions by CPTU. Biogeotechnics, 3(1), 100131.

Girshick, R. (2015). Fast R-CNN. In Proceedings of ICCV.

Li, X., Yin, L., Chen, W., Gao, Z., & Liu, X. (2017). A high-resolution tunneling magneto-resistance sensor interface circuit.Modern Physics Letters B,31(04), 1750030.

Li, X., Chen, W., Yin, L., Fu, Q., & Liu, X. (2017). A closed-loop Sigma-Delta modulator for a tunneling magneto-resistance sensor.IEICE Electronics Express,14(15), 20170700-20170700.

Malik, B. A., Mandhaniya, P., Soni, A. K., & Ouyang, Z. (2024). Numerical modeling and failure analysis of caisson foundations subjected to the monotonic lateral loads. Ocean Engineering, 309, 118491.

Yang, Y., Liao, Y. H., Bortins, I., Baldwin, D. P., & Zhang, S. (2024). Unidirectional structured light system calibration with auxiliary camera and projector.Optics and Lasers in Engineering,175, 107984.

Yu, Y., Zhang, L., Wang, B., Zhao, J., Han, K., Qi, Y., ... & Wang, W. (2025). Synergistic π-Tunnel Clamps in β-Sheets for Long-Range Dry-State Conduction: Toward Neural Restoration. Journal of the American Chemical Society, 147(13), 11049-11061.

Tian, Y., & Yang, Z. (2026, May). SAEC: scene-aware enhanced edge-cloud collaborative industrial vision inspection with multimodal LLM. In ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 19747-19751). IEEE.

Wang, S., Wang, J., Song, C., Wen, J., & Tu, J. (2020). Numerical investigation on the effects of operating conditions and configuration parameters in industrial risers. Powder Technology, 363, 265-274.

Jie, S., Malik, B. A., Liang, Z., Duan, M., & Ouyang, Z. (2025, June). Effects of Installation on Lateral Bearing Capacity of Modified Suction Caissons with External Skirted Structure. In ISOPE International Ocean and Polar Engineering Conference (pp. ISOPE-I). ISOPE.

Ansari, A., Mandhaniya, P., Malik, B. A., & Ouyang, Z. (2025). Disaster risk and resilience assessment of multi-utility transportation infrastructure and urban projects. Frontiers in Built Environment, 11, 1619407.

Szegedy, C., Vanhoucke, V., Ioffe, S., Shlens, J., & Wojna, Z. (2016). Rethinking the Inception architecture for computer vision. In Proceedings of CVPR.

Yu A, Pang F, Yuan Y, et al. Simultaneous current and vibration measurement based on interferometric fiber optic sensor[J]. Optics & Laser Technology, 2023, 161: 109223.